



EN ISO 20345:2022 

DIVENTURE
MARMOLADA
70539-05L

S7S FO *CI SC LG SR

Size: 36-48
Weight: 750 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Oil industry, Farming and
 Gardening



FEATURES

UPPER
 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Reflex insert

LINING
 3D Green Air 320 gr.

ANTISLIP LINING
 DUALMICRO

INSOLE
 QRS02 Green

TOE CAP
 Fiber cap SXT

RESISTANCE TO PERFORATION
 KX Antiperforation recycled PS

TYPE
 Ankle boot

SOLE
PU DUAL-DENSITY CCYCLED® SR
 Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.



TECHNOLOGIES

Removable Insole
QRS02 GREEN

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements

KX GREEN RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other
HDry
 +WATERPROOF UPPER

The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

